

PALAVRAS CHAVES/KEY WORDS

AUTORES / AUTHORS: DIGITAL ELEVATION MODELS  
ATMOSPHERIC REFRACTION VISIBILITY  
EARTH'S CURVATURE

AUTORIZADA POR/AUTHORIZED BY  
*Múcio Roberto Dias*  
Múcio Roberto Dias  
Vice Director General

AUTOR RESPONSÁVEL / RESPONSIBLE AUTHOR  
*Ewerton Santos Silva*  
Ewerton Santos Silva

DISTRIBUIÇÃO/DISTRIBUTION

INTERNA / INTERNAL  
 EXTERNA / EXTERNAL  
 RESTRITA / RESTRICTED

REVISADA POR / REVISED BY

CDU/UDC  
528.8

DATA / DATE  
March 1990

TÍTULO/TITLE	PUBLICAÇÃO Nº PUBLICATION NO <b>INPE-5044-PRE/1574</b>
	DIGITAL ELEVATION MODEL VISIBILITY INCLUDING EARTH'S CURVATURE AND ATMOSPHERE REFRACTION
AUTORES/AUTHORSHIP	Ewerton Santos Silva (*) Luiz Alberto Vieira Dias

ORIGEM / ORIGIN  
LAC

PROJETO / PROJECT  
INBM

Nº DE PAG. / NO OF PAGES  
10

ULTIMA PAG. / LAST PAGE  
07

VERSÃO / VERSION

Nº DE MAPAS / NO OF MAPS

RESUMO - NOTAS / ABSTRACT - NOTES

There are some instances in which the Earth's curvature and the atmospheric refraction, optical or electronic, are important factors when Digital Elevation Models are used for visibility calculations. This work deals with this subject, suggesting a practical approach to solve this problem. Some examples, from real terrain data are presented. The equipment used was an IBM-PC like computer with a SITIM graphics card.

OBSERVAÇÕES / REMARKS

This paper will be submitted to the International Society of Photogrammetry and Remote Sensing (ISPRS), Tsukuba, Japan, May 15-18, 1990.  
(\* ) Centro de Cartografia Automatizada do Exército-Brasília-DF

## RESUMO

Há casos em que a curvatura da Terra e/ou a refração atmosférica, ótica ou eletrônica, são fatores importantes quando Modelos Digitais de Elevação são usados para cálculos de visibilidade. Este trabalho trata deste assunto, sugerindo uma abordagem prática para sua solução. Alguns exemplos, a partir de dados de um terreno real são apresentados para ilustração. O equipamento usado foi um computador compatível com um IBM-PC, com uma placa gráfica SITIM.



DIGITAL ELEVATION MODEL VISIBILITY INCLUDING EARTH'S  
CURVATURE AND ATMOSPHERE REFRACTION

Ewerton Santos Silva  
Centro de Cartografia Automatizada do Exército  
60000 - Brasília - DF - BRAZIL

Luiz Alberto Vieira Dias  
Institute for Space Research - INPE  
Caixa Postal 515 - 12201 - São José dos Campos-SP-BRAZIL

Abstract

There are some instances in which the Earth's curvature and the atmospheric refraction, optical or electronic, are important factors when Digital Elevation Models are used for visibility calculations. This work deals with this subject, suggesting a practical approach to solve this problem. Some examples, from real terrain data, are presented. The equipment used was an IBM-PC like computer with a SITIM graphics card.

KEY WORDS: Digital Elevation Models, Earth's Curvature,  
Atmospheric Refraction, Visibility.

1. INTRODUCTION

When Digital Elevation Models (DEM) are used for site selection of FM radio or TV stations transmission towers, in addition to the Earth's curvature, the atmospheric refraction also has to be taken into account. This is due to the fact that VHF (very high frequency - 30 Mz to 300 MHz) radio waves are refracted by the Earth's atmosphere because the atmospheric density varies with height causing the radio waves to bend towards the ground. Even when the location of visual observation forest fire control posts have to be chosen, the above discussed effects also have to be considered, with the use of an optical refraction index. To develop a computer software that, using, a DEM, is capable of calculating the visibility for a given observer situated at a certain height above the ground, with Earth's curvature and atmospheric refraction effects, was the main objective of this work. Such a software, running on MS-DOS on a IBM-PC-XT clone computer, with a SITIM graphics card, is an addition to the Geographic Information System developed at the Institute for Space Research-INPE, Brazil (1,2). The SITIM card was also developed at INPE.

The software is flexible enough to allow the user to change the Earth's radius and the refractive index, K. It should be noticed that a possible application, not attempted on this work, is the use of this software for visibility calculations on planets and/or satellites with a different radius and/or different atmosphere.

## 2. FLAT EARTH, NO REFRACTION

The method to determine the visibility here presented is based on Yoeli (3), with  $XO$  and  $YO$  as the observation point coordinates,  $TO$  as the observer height above the ground,  $DX$  and  $DY$  as the intervals between columns and lines, respectively, then the observation point altitude,  $ZO$ , is the interpolated altitude  $HO$ , plus  $TO$ .

The interpolation used for the observation point is:

$$HO = \frac{\sum_i (H_i/D_i^2)}{\sum_i (1/D_i)}, \text{ and } ZO = HO + TO$$

where,  $i=1, \dots, 4$  are the four cell vertexes,  $D_i$  the distance of the point to each of the vertexes,  $H_i$  the altitude at each vertex. The DEM x and y coordinates are given by:

$$XP = XO + DX (I-1), \text{ and } YP = YO + DY (J-1)$$

with  $I = 1, \dots, N$  (column number), and  $J = 1, \dots, K$  (line number).

The visibility will be determined only for the DEM points, in order to simplify the calculations. The observer point is O and the point to be observed is P.

For visibility determination the following algorithm is applied:

- a) If all the intermediate point between O and P have smaller altitudes than the end points, P is visible.
- b) If at least one of the intermediate points between O and P have a higher altitude than the end points, P is invisible.
- c) If the steps a) and b) could not determine the visibility, calculate the tangent with respect to the horizon, between O and P, and O and all the intermediate points. If at least one of the tangents is larger than the tangent between O and P, the point P is invisible, on the contrary P is visible.

The visibility is determined for all points of the region, and the result is stored on a binary matrix: 1-visible, 0-unvisible. Each matrix element corresponds to a DEM cell. The matrix is then displayed graphically, along with a legend for the parameters used.

### 3. CURVED EARTH, REFRACTION

Since the Earth is not flat, its curvature effect have to be included. Form geometry, the target P sinks by a value e:

$$e = d^2 / (2R)$$

where d is the distance between O and P and R is the Earth's radius.

On the other hand, the electromagnetic radiation bends down, the value of the bending depends on the refraction index, K. For visible light the average value for K, in Brazil, is 0.13 (4), while for microwaves is 0.25 (5), and for VHF 1.3 (6). The vertical value that has to be added to the altitude of P due to refraction is r:

$$r = d^2 * K / (2R)$$

where K is the refraction index.

Based on the above , the correction on the DEM becomes:

$$Z_P = Z_O - d^2 * (K-1) / (2R)$$

Then the DEM altitude matrix may be corrected to include the Earth's curvature and/or the refraction.

### 4. EXPERIMENTAL RESULTS

It was chosen an area near Campinas, SP, Brazil to test the software. The size of the region is 8x8 kilometers, with a DEM of 161 lines x 161 columns with 50 meter horizontal and vertical resolution. Figure 1 presents a perspective view of the region DEM, with a vertical exaggeration of 30 times.

